

Permit for Sewer Connection

The Municipality of the County of Kings PO Box 100, 87 Cornwallis St., Kentville NS B4N 3W3 Phone: (902)690-6195 Fax: (690)679-0911 www.county.kings.ns.ca

| Perm | it I | No. |
|------|------|-----|
| | | 10. |

Note: Sewer Permit Valid only one year from Approval Date

| OWNER INFORMATION | | | |
|---|--|-----------------------|----------------------------|
| | | | |
| Owner | | | Home phone |
| OWNER | | | Home phone |
| | | | |
| Mailing Address | Community | | Work phone |
| | | | |
| Province | Postal Code | | Cell phone |
| CONTRACTOR INFORMATION | | | |
| | | | |
| Name | | | Cell phone |
| | | | |
| | | | |
| Company | | | Office phone |
| SERVICE CONNECTION | | | |
| | | | |
| Civic Street | | | PID |
| | | | |
| Sewer System (Note: Single connection for Av | onport is \$4000: Greenwich Ro | I. S. is \$4000: and. | AA |
| Wolfville Ridge Hamlet is \$5000.) | · | | |
| | No. of connections Lateral to be installed Use Description (from | | ilding Permit) |
| on property (Check one) | | | |
| I Existing I I | existing | | |
| After work Size | □ in. | | |
| complete | □ mm | | |
| Purpose of Lateral (check all that apply) | | Type of Wastewat | er (check all that apply) |
| | estaurant (seating capacity) | □ Domestic | cr (crieck an triat apply) |
| ☐ Duplex/Semi-Detached | | | Type of facility) |
| | ar (seating capacity) | | s (Type of facility) |
| 1 · | office (# of employees) | ☐ Commercia | |
| ☐ Motel (# of beds) ☐ C | ther | Other (Plea | se state) |
| Attach location plan OR | | Engineering & P | ublic Works Use Only |
| Sketch lot , building footprint, road frontag | ge and location of sewer | | |
| main (if known) indicating distances Distances shown in □ ft □ m | | C | |
| Distances snown in 🗆 it 🗆 m | | Comments: | |
| | Indicate North | | |
| | | | |
| | A | | |
| | $\mathbf{x}^{\top}\mathbf{x}$ | | |
| | ← | | |
| | ∠ | | |
| | • | | |
| | | | |
| Expected start date of construction: | | Connection | ☐ Paid |
| · | | charge \$_ | · |
| I hereby declare this information to be true | accurate and complete | | |
| to the best of my knowledge. | | | |
| | | Engineer Approval | Date |
| | | | |
| Signature of Applicant | Date | Municipal Tax O | |
| Sewer Code Annual Sewer Rate | | | |
| PERMIT NOT VALID UNLESS PA | AGE 2 SIGNED | | |

THE MUNICIPALITY OF KINGS COUNTY "GUIDELINES FOR INSTALLATION OF SEWER LATERALS ON PRIVATE PROPERTY"

The following guidelines are intended for use by Municipal Staff conducting inspections on service laterals prior to backfilling.

These guidelines are only to be applied to that portion of the lateral located on private property that extends from the property line to the building connection. For sewer laterals owned by the Municipality within either the road right of way or an easement, refer to the *Municipal Services Specification Manual*.

- 1. Recommended minimum grade on a lateral is 1% (one foot of grade in 100 feet) discretion may be exercised to reduce the grade to 0.75% (9" in 100 feet) if required to avoid pumping or maintain depth of cover.
- Recommended minimum depth of a lateral is four feet under a driveway and three feet below other areas. Discretion may be used to avoid pumping but in any event, the lateral must be protected from frost.
- 3. Clean-outs are required for lengths greater than 75 feet, measured to the main line.
- 4. Minimum size is four-inch diameter and pipe must be a PVC SDR35 minimum, bell and spigot gasket joint.
- 5. Pipe must be installed with bells facing "uphill" in the direction of the dwelling.
- 6. The pipe must rest on Type A gravel.
- 7. For pipe less than 6 iches in diameter:
 - a. Bends must be long radius bends (no more than 5 degrees every 10 feet) OR using a maximum of one 45 degree elbow or two 22.5 degree elbows.
 - b. Lateral must be connected at an angle of 45 degrees above the horizontal of the sewer main.
- 8. For laterals greater than 6 inches in diameter:
 - a. Lateral must be connected to a manhole (not the sewer main).
 - b. No bends between building and manhole are permitted.
- 9. A **backwater** valve must be installed to protect every fixture or drain located below the level of the street, according to the Canadian Plumbing Code.
- 10. If a pump is required, it must be protected with a double check valve assembly.
- 11. Care should be taken to locate the lateral away from utility poles, trees and other forms of shrubbery.
- 12. Existing septic tanks must be by-passed before connection to the municipal sewer.
- 13. It is recommended that septic tanks be pumped and removed or filled with appropriate material. Contact the N.S. Department of the Environment for requirements.

THE INSTALLATION MUST BE INSPECTED PRIOR TO BACKFILLING. THE HOURS OF INSPECTIONS ARE BETWEEN 8:30 AM AND 4:00 PM, MONDAY TO FRIDAY. NOTIFY THE MUNICIPALITY 24 HOURS IN ADVANCE OF ANY INSTALLATION (902) 690-6195.

BY-LAW #27B SEWER CONNECTION BY-LAW

- This by-law shall be known as and may be cited as the "Sewer Connection By-Law".
- 2. In this by-law:
 - (a) "Owner" means a part owner, joint owner, tenant in common or joint tenant of the whole or any part of any land or building and includes a trustee, an executor, an administrator, a guardian, an agent, a mortgagee in possession or other person having the care or control of any land or building in case of the absence or disability of the person having the title thereto:
 - (b) "Sewer Line" means a sewer or drainage system constructed, purchased or otherwise acquired by the Municipality and maintained as a public sewer or drain.
- 3. The Council may by resolution order the owner of every dwelling house, shop, store, office or other building the nearest part of which is not more than one hundred feet from any portion of a sewer line to construct at his own expense a drain therefrom and connect the same with the sewer line.
- 4. Each drain ordered by the Council to be constructed under Section 3 shall be constructed subject to the supervision of the Municipal Engineer or other competent person authorized by the Municipal Clerk (hereinafter referred to as the Municipal Authority) and shall be of such size and at such level and descent and with such mode of piercing or opening into the sewer, and generally in such manner and of such materials, as the Municipal Authority directs, and no such drain shall be covered in until it has been inspected and approved by the Municipal Authority.
- The Council shall not make an order under Section 3 against any person until service from the sewer line has been available for the property of that person for one year.
- 6. Where an order has been made by the Council under Section 3 or where the building is connected with the sewer line the Council may by resolution order the owners of outhouses and septic tanks to remove such outhouses and to destroy and fill such septic tanks.
 - (1) Any person who fails to comply with an order made under Section 3 or Section 6 within thirty days after notice thereof has been serviced upon him either personally or by registered mail addressed to the last address known to the Municipal Clerk, is guilty of an offence and liable on summary conviction to a penalty not exceeding five hundred dollars and in default of payment to imprisonment for a period of not exceeding three months.
 - (2) Every day during which such failure to comply continues shall be deemed a fresh offence.

| I hereby agree to comply with the Sewer By-Law of the Mu | unicipality of the County of Kings as well as the Guidelines for |
|--|--|
| Installation of Sewer Laterals on Private Property as shown al | bove. |

| APPLICANT'S SIGNATURE: | DATE: |
|------------------------|-------|
|------------------------|-------|